

PRODUCT DATASHEET

ENDURA Style Midi Spot I 13.5W

ENDURA® STYLE MIDI SPOT | Wall luminaires with rotatable head



Areas of application

- Outdoor use (IP44)
- Building facades
- Entrance lighting
- Patios, balconies

Product benefits

- Easy and quick installation
- Energy-efficient thanks to LED technology

Product features

- Rotation angle luminaire head: 320°, swiveling: 75°
- Die-cast aluminum housing



TECHNICAL DATA

Electrical data


| | |
|------------------------|-------------------------------|
| Nominal wattage | 13.50 W |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Nominal current | 75.000 mA |
| Power factor λ | > 0.5 |
| Protection class | I |
| Operating mode | Electronic control gear (ECG) |

Photometrical data

| | |
|--|----------------------|
| Luminous flux | 800 lm |
| Total luminous flux of contained light sources | 1450 lm |
| Luminous efficacy | 62 lm/W |
| Color temperature | 3000 K |
| Light color (designation) | Warm White |
| Color rendering index Ra | ≥ 80 |
| Standard deviation of color matching | < 6 sdc _m |
| Beam angle | 110 ° |

Dimensions & Weight

| | |
|----------------|-----------|
| Length | 162.00 mm |
| Width | 125.00 mm |
| Height | 128.00 mm |
| Product weight | 700.00 g |



Materials & Colors

| | |
|---------------|-----------|
| Product color | Dark gray |
| Housing color | Dark gray |

| | |
|-----------------|-------------------------------|
| Body material | Aluminum |
| Cover material | Polymethylmethacrylate (PMMA) |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|------------------------------|-----------------|
| Ambient temperature range | -20...+40 °C |
| Temperature range at storage | -30...+70 °C |
| Type of connection | Screw terminal |
| Type of protection | IP44 |
| Dimmable | No |
| Mounting type | Surface |
| Mounting location | Wall / Ceiling |
| Application environment | Outdoor |
| LED module replaceable | Not replaceable |

Lifespan

| | |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C | 50000 h |
| Number of switching cycles | 15000 |




Certificates & Standards

| | |
|-----------|-----------------|
| Standards | CE / EAC / UKCA |
|-----------|-----------------|

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

DOWNLOAD DATA

| DOWNLOAD DATA | |
|--|-------------------------------|
|  | User instruction |
|  | Declarations Of Conformity CE |
|  | Packaging insert |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075205475 | Folding box 1 | 154 mm x 154 mm x 181 mm | 724.00 g | 4.29 dm ³ |
| 4058075205482 | Shipping box 6 | 478 mm x 325 mm x 192 mm | 4587.00 g | 29.83 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.