



WEVER & DUCRÉ
LIGHTING

SOLID petit 1.0

133864W3

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Surface

Signal White

IP20

Interior

325 lm

RAL 9003^a

LED

2700 K

CRI 90

L80 B50 / 50000h

2-step binning

OPTICAL

Beam angle 32°

PHYSICAL

Diameter 60 mm

Height 130 mm

0.32 kg

ELECTRICAL

phase-cut dim


220 - 240 V

Total connected power 6 W


Class 1

Safety distance 0.3 m


^a Color may deviate slightly due to production conditions.



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Signal White; powder coated; matt texture; RAL 9003; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; phase-cut dim; light colour 2700 K; binning initial MacAdam 2 SDCM; CRI 90; 220 - 240 V; beam angle 32°; degree of protection IP20; PC1; power supply included; light source replaceable by an authorized professional; control gear replaceable by end-user;



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

SOLID petit 1.0

133864W3

CONE DIAGRAM

30°

h (m)	E0° (lx)	ø (m)
1	942	0.54
2	235	1.07
3	105	1.61
4	59	2.15
5	38	2.68