



WEVER & DUCRÉ
LIGHTING

PIRRO OPAL 4.0

151484E3

Project
Type
Notes
Quantity
Date

GENERAL

Ceiling
Surface
Signal White + Jet Black
IP20
Interior
550 lm
RAL 9003 + RAL 9005^a

LED

2700 K

OPTICAL

Opal


PHYSICAL

Length 182 mm
Width 50 mm
Height 65 mm
0.52 kg


ELECTRICAL

phase-cut dim
220 - 240 V
Total connected power 12 W
Class 1
Safety distance 0.3 m

^a Color may deviate slightly due to production conditions.



Rectangular ceiling surface mounted downlight made from die-cast aluminium with opal PMMA cover; surface housing Signal White powder coated; matt texture; with aesthetic frame in Jet Black wet painted; matt fine texture; PCB 3-step binning; phase-cut dim; light colour 2700 K; CRI (Colour Rendering Index) 90; CRI (Colour Rendering Index) 90; degree of protection IP20; PC1; power supply included; light source replaceable by an authorized professional; control gear replaceable by end-user;





WEVER & DUCRÉ
LIGHTING

PIRRO OPAL 4.0

151484E3

MOUNTING

1.0 CEILING BASE

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
PIRRO SYSTEM	White	755-51-12	9 0 0 5 2 0 7 2
PIRRO SYSTEM	Black	755-51-12	9 0 0 5 2 0 7 3
PIRRO SYSTEM	Gold	755-51-12	9 0 0 5 2 0 7 4

2.0 CEILING BASE

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
PIRRO SYSTEM	White	1150-51-12	9 0 0 5 2 0 7 5
PIRRO SYSTEM	Black	1150-51-12	9 0 0 5 2 0 7 6
PIRRO SYSTEM	Gold	1150-51-12	9 0 0 5 2 0 7 7