



WEVER & DUCRÉ
LIGHTING

TUBE 1.0 PAR16

734120W0

Project
Type
Notes
Quantity
Date

GENERAL

Ceiling
 Surface
 Signal White
 IP65
 Exterior
 355^a to 360^b lm
 RAL 9003^c

LED

Lamp PAR16
 PAR16
 Socket GU10
 max. 5 W
 CRI 80

OPTICAL

Beam angle 38°

PHYSICAL

Diameter 80 mm
 Height 105 mm
 0.6 kg


ELECTRICAL

phase-cut dim
 100 - 240 V
 Total connected power 4.1^b to 4.8^a W
 Class 1
 Safety distance 0.3 m


^a PAR16 LED 2700K CRI 80 silver
^b LED 3000K CRI 80 silver
^c Color may deviate slightly due to production conditions.



IP65 $\le 38^\circ$



LIGHT DISTRIBUTION



[734120W0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
 © Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

TUBE 1.0 PAR16

734120W0

CONE DIAGRAM

PAR16 LED 2700K CRI ≥ 80

h (m)	E0° (lx)	Ø (m)
1	640	0.68
2	160	1.37
3	71	2.05
4	40	2.74
5	26	3.42

LAMPS

PAR16 LED Lamp

TYPE	Ø · H (MM)	ORDERCODE
2700K >80 CRI GU10	∅50 · 52	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	∅50 · 52	9 0 5 2 2 7 S 4